

Trimble RTS673

ROBOTIC TOTAL STATION

ACCURACY FOR EVERYDAY APPLICATIONS

With the Trimble® RTS673 Robotic Total Station contractors can improve efficiency and accuracy for common layout tasks in building construction.

For Everyday Layout

Automate building layout tasks with total confidence. The Trimble RTS673 streamlines layout of sleeves, hangers, stub-up or cable trays. Versatile enough for light topographic projects and as-built data collection, the RTS655 can handle almost any challenge on the job site.

UNSURPASSED TOTAL STATION TECHNOLOGY

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

Trimble MultiTrack™ technology locks on and tracks passive prisms for control measurements and active targets for dynamic measurement, stakeout and grade control.

BUILT FOR CONSTRUCTION

- ▶ For construction applications, you need a measurement solution with optimal speed, accuracy and reliability. With the Trimble DR HP Precision EDM you have the flexibility to tackle the most demanding projects.
- ▶ Visually mark points, with high precision, using the Class 2 Laser Pointer.
- ▶ Automatic Servo Focus sets the optical focus for quick manual aiming when laying out points in DR mode.
- ▶ Combine with Trimble Field Link software running on the Trimble Field Tablet to optimize your accuracy and productivity.

Key Features

- ▶ MagDrive technology for maximum speed and efficiency
- ▶ MultiTrack technology offers the choice between passive and active tracking
- ▶ Quickly mark layout points with Class 2 laser Pointer
- ▶ Lock onto your target faster in robotic mode with Track-Light technology



Trimble RTS673 ROBOTIC TOTAL STATION

PERFORMANCE

Angle measurement accuracy
(standard deviation based on ISO 17123-3) 3" (0.9 mgon)
Angle display (least count) 0.1" (0.01 mgon)
Distance measurement

Typical Accuracy	50 m (164 ft)	100 m (328 ft)	200 m (656 ft)	300 m (984 ft)
Prism mode				
Standard	2 mm (5/64")	3 mm (1/8")	4 mm (5/32")	6 mm (15/64")
Tracking	5 mm (13/64")	5 mm (13/64")	6 mm (15/64")	8 mm (5/16")
DR mode				
Standard	3 mm (1/8")	4 mm (5/32")	5 mm (13/64")	6 mm (5/64")
Tracking	10 mm (25/64")	10 mm (25/64")	11 mm (7/16")	12 mm (15/32")

Measuring time

Prism mode
Standard 3 s
Tracking 0.4 s
Averaged observations 3 s per measurement
DR mode
Standard 3–15 s
Tracking 0.4 s

Range (under standard clear conditions^{1,2})

Prism mode
1 prism 3,000 m (9,800 ft)
Shortest range 1.5 m (4.9 ft)

DR mode

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective) ³	> 150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
Gray card (18% reflective) ³	> 120 m (394 ft)	120 m (394 ft)	50 m (164 ft)

Shortest range 1.5 m (4.9 ft)

EDM SPECIFICATIONS

Light source Laser diode 660 nm; Laser class 1 in Prism mode
Laser class 2 in DR mode

Laser pointer coaxial (standard) Laser class 2

Beam divergence Prism mode

Horizontal 4 cm/100 m (0.13 ft/328 ft)
Vertical 4 cm/100 m (0.13 ft/328 ft)

Beam divergence DR mode

Horizontal 2 cm/50 m (0.066 ft/164 ft)
Vertical 2 cm/50 m (0.066 ft/164 ft)

Atmospheric correction -130 ppm to 160 ppm continuously

GENERAL SPECIFICATIONS

Leveling

Circular level in tribrach 8/2 mm (8/0.007 ft)

Automatic level compensator

Type Centered dual-axis
Accuracy 0.5" (0.15 mgon)
Range ±5.4' (±100 mgon)

Servo system MagDrive servo technology, integrated servo/angle sensor; electromagnetic direct drive

Rotation speed 115 degrees/s (128 gon/s)

Rotation time Face 1 to Face 2 2.6 s

Positioning speed 180 degrees (200 gon) 2.6 s

Clamps and slow motions Servo-driven, endless fine adjustment

Centering

Centering system Trimble 3-pin

Optical plummet Built-in optical plummet

Magnification/shortest focusing distance 2.3×/0.5 m to infinity
(1.6 ft to infinity)

Telescope

Magnification 30×

Aperture 40 mm (1.57 in)

Field of view at 100 m (328 ft) 2.6 m at 100 m (8.5 ft at 328 ft)

Shortest focusing distance 1.5 m (4.92 ft) to infinity

Illuminated crosshair Variable (10 steps)

Autofocus Standard

Tracklight built in Not available in all models

Operating temperature -20° C to +50° C (-4° F to +122° F)

Dust and water proofing IP55

Humidity 100% condensing

Power supply

Internal battery Rechargeable Li-Ion battery 10.8V, 6.5Ah, 70Wh

Operating time⁴

One internal battery Approx. 6.5 hours

Three internal batteries in multi-battery adapter Approx. 18 hours

Robotic holder with one internal battery 13.5 hours

Operating time with video robotic⁴

One battery 5.5 hours

Three batteries in multi-battery adapter 17 hours

Weight

Instrument (Servo/Autolock[®]) 5.15 kg (11.35 lb)

Instrument (Robotic) 5.25 kg (11.57 lb)

Trimble CU controller 0.4 kg (0.88 lb)

Tribrach 0.7 kg (1.54 lb)

Internal battery 0.35 kg (0.77 lb)

Trunnion axis height 196 mm (7.71 in)

Communication USB, Serial, Bluetooth[®]

Security Dual-layer password protection

ROBOTIC RANGE

Autolock and Robotic range²

Passive prisms 500–700 m (1,640–2,297 ft)

Trimble MultiTrack Target 800 m (2,625 ft)

Autolock pointing precision at 200 m (656 ft) (standard deviation)²

Passive prisms <2 mm (0.007 ft)

Trimble MultiTrack[™] Target <2 mm (0.007 ft)

Shortest search distance 0.2 m (.65 ft)

Search time (typical)⁶ 2–10 s

1 Standard clear: No haze. Overcast or moderate sunlight with very light heat shimmer.

2 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.

3 Kodak Gray Card, Catalog number E1527795.

4 The capacity in -20° C (-5° F) is 75% of the capacity at +20° C (68° F).

5 Bluetooth type approvals are country specific. Contact your local

Trimble Authorized Distribution Partner for more information.

6 Dependent on selected size of search window.



Specifications subject to change without notice.