

Trimble RTS773

ROBOTIC TOTAL STATION

TOTAL PERFORMANCE

The RTS773 incorporates advanced technologies to deliver accurate and reliable layout fast, to ensure that design intent is executed correctly the first time.

Video-Assisted Control

Trimble VISION™ gives you the power to see everything the instrument sees without a trip back to the tripod. Direct your layout with live video images on the Trimble Field Tablet. Now you are free to capture measurements, to prism or reflectorless surfaces, with point and click efficiency.

Visual Verification

To provide an accurate documentation of the design and field image that is displayed within the Trimble Field Link software, job data including points and linework are overlaid on the camera image.

LAYOUT TECHNOLOGY FOR CONTRACTORS

Trimble MagDrive™ Servo Technology provides for exceptional speed and accuracy with smooth, silent operation.

Trimble SurePoint™ Technology ensures accurate measurements by automatically correcting for unwanted movement due to wind, sinkage, and other factors.

Trimble MultiTrack™ technology locks on and tracks passive prisms for control measurements and active targets for dynamic measurement, stakeout and grade control.

BUILT FOR CONSTRUCTION

For construction applications, you need a measurement solution with optimal speed, accuracy and reliability. Combine the Trimble DR HP Precision EDM with Trimble VISION and you have the flexibility to tackle the most demanding projects.

- ▶ Visually mark points, at greater range, with the Class 2 Laser Pointer.
- ▶ **Automatic Servo Focus** sets the optical focus for quick manual aiming when laying out points in DR mode.
- ▶ Combine with Trimble Field Link software running on the Trimble Field Tablet to optimize your accuracy and productivity.

Key Features

- ▶ Trimble VISION video-assisted robotic measurement
- ▶ Visual verification with data overlay and photo documentation
- ▶ MagDrive technology for maximum speed and efficiency
- ▶ MultiTrack technology offers the choice between passive and active tracking



Trimble RTS773 ROBOTIC TOTAL STATION

PERFORMANCE

Angle measurement accuracy
(standard deviation based on ISO 17123-3) 3" (0.9 mgon)
Angle display (least count) 0.1" (0.01 mgon)
Distance measurement

Typical Accuracy	50 m (164 ft)	100 m (328 ft)	200 m (656 ft)	300 m (984 ft)
Prism mode				
Standard	2 mm (5/64")	3 mm (1/8")	4 mm (5/32")	6 mm (15/64")
Tracking	5 mm (13/64")	5 mm (13/64")	6 mm (15/64")	8 mm (5/16")
DR mode				
Standard	3 mm (1/8")	4 mm (5/32")	5 mm (13/64")	6 mm (15/64")
Tracking	10 mm (25/64")	10 mm (25/64")	11 mm (7/16")	12 mm (15/32")

Measuring time
Prism mode
Standard 3 s
Tracking 0.4 s
Averaged observations 3 s per measurement
DR mode
Standard 3–15 s
Tracking 0.4 s
Range (under standard clear conditions^{1,2})
Prism mode
1 prism 3,000 m (9,800 ft)
Shortest range 1.5 m (4.9 ft)
DR mode

	Good (Good visibility, low ambient light)	Normal (Normal visibility, moderate sunlight, some heat shimmer)	Difficult (Haze, object in direct sunlight, turbulence)
White card (90% reflective) ³	>150 m (492 ft)	150 m (492 ft)	70 m (229 ft)
Gray card (18% reflective) ³	>120 m (394 ft)	120 m (394 ft)	50 m (164 ft)

Shortest range 1.5 m (4.9 ft)

EDM SPECIFICATIONS

Light source Laserdiode 660 nm; Laser class 1 in Prism mode
Laser class 2 in DR mode
Laser pointer coaxial (standard) Laser class 2
Beam divergence Prism mode
Horizontal 4 cm/100 m (0.13 ft/328 ft)
Vertical 4 cm/100 m (0.13 ft/328 ft)
Beam divergence DR mode
Horizontal 2 cm/50 m (0.066 ft/164 ft)
Vertical 2 cm/50 m (0.066 ft/164 ft)
Atmospheric correction -130 ppm to 160 ppm continuously

CAMERA

Chip Color Digital Image Sensor
Resolution 2048 x 1536 pixels
Focal length 23 mm
Depth of field 3 m to infinity
Field of view 15.5 deg x 12.3 deg
Digital zoom 4-step (1x, 2x, 4x, 8x)
Video streaming 5 frames/sec

GENERAL SPECIFICATIONS

Leveling
Circular level in tribrach 8"/2 mm (8"/0.007 ft)
Automatic level compensator
Type Centered dual-axis
Accuracy 0.5" (0.15 mgon)
Range ±5.4' (±100 mgon)
Servo system MagDrive servo technology, integrated
servo/angle sensor; electromagnetic direct drive
Rotation speed 115 degrees/s (128 gon/s)
Rotation time Face 1 to Face 2 2.6 s
Positioning speed 180 degrees (200 gon) 2.6 s
Clamps and slow motions Servo-driven, endless fine adjustment
Centering
Centering system Trimble 3-pin
Optical plummet Built-in optical plummet
Magnification/shortest focusing distance 2.3x/0.5 m to infinity
(1.6 ft to infinity)
Telescope
Magnification 30x
Aperture 40 mm (1.57 in)
Field of view at 100 m (328 ft) 2.6 m at 100 m (8.5 ft at 328 ft)
Shortest focusing distance 1.5 m (4.92 ft) to infinity
Illuminated crosshair Variable (10 steps)
Autofocus Standard
Operating temperature -20° C to +50° C (-4° F to +122° F)
Dust and water proofing IP55
Humidity 100% condensing
Power supply
Internal battery Rechargeable Li-Ion battery 10.8V, 6.5Ah, 70Wh
Operating time⁴
One internal battery Approx. 6.5 hours
Three internal batteries in multi-battery adapter Approx. 18 hours
Robotic holder with one internal battery 13.5 hours
Operating time with video robotic⁴
One battery 5.5 hours
Three batteries in multi-battery adapter 17 hours
Weight
Instrument (Servo/Autolock*) 5.15 kg (11.35 lb)
Instrument (Robotic) 5.25 kg (11.57 lb)
Trimble CU controller 0.4 kg (0.88 lb)
Tribrach 0.7 kg (1.54 lb)
Internal battery 0.35 kg (0.77 lb)
Trunnion axis height 196 mm (7.71 in)
Communication USB, Serial
Security Dual-layer password protection
ROBOTIC RANGE
Autolock and Robotic range²
Passive prisms 500–700 m (1,640–2,297 ft)
Trimble MultiTrack Target 800 m (2,625 ft)
Autolock pointing precision at 200 m (656 ft) (standard deviation) Passive prisms <2 mm (0.007 ft)
Trimble MultiTrack™ Target <2 mm (0.007 ft)
Shortest search distance 0.2 m (.65 ft)
Search time (typical)⁵ 2–10 s

- 1 Standard clear; No haze. Overcast or moderate sunlight with very light heat shimmer.
- 2 Range and accuracy depend on atmospheric conditions, size of prisms and background radiation.
- 3 Kodak Gray Card, Catalog number E1527795.
- 4 The capacity in -20 °C (-5 °F) is 75% of the capacity at +20 °C (68 °F).
- 5 Dependent on selected size of search window.

Specifications subject to change without notice.

